

QTA 1000 SERIES single channel power amplifiers

Commercial audio for professionals.

Public address amplifiers could be said to be the utility end of the audio market, working anonymously day after day in a dusty cupboard or equipment space. Quite invisible to all until one fails. It is amazing how quickly "no sound" reverberates up the business chain of command to impose itself on the unfortunate contractor who has supplied the faulty equipment.

Quest commercial audio is manufactured to the same exacting standards as the live audio products

This is why Quest offer such a wide range of commercial Amplifiers. There's a model for every situation A range of pro features makes the Quest QTA series an easy choice for contractors who need flexibility of sound design options and easy installation



QTA-1120P power amp

- Output Power (RMS): 120W
- Power Supply: Main Voltage: AC 115V or 230V 50/60Hz, Battery Voltage: DC 24V
- Total Harmonic Distortion: $\leq 1\%$ @ 1KHz, rated power
- Sensitivity: XLR, Phone Jack (Balanced) 1V, 100mV @ 10K Ω
- Outputs: 8 Ω , 70V, 100V
- Signal to Noise Ratio: 86 dB
- Indicator: Power On, Level
- AC Power Consumption: 320W
- DC Power Consumption: 8A
- Dimensions (mm): 88(H) x 425(W) x 305(D)
- Weight: 8.2 Kg
- Mounting options: Desktop or 19" rack



QTA-1240P power amp

- Output Power (RMS): 240W
- Power Supply: Main Voltage: AC 115V or 230V 50/60Hz, Battery Voltage: DC 24V
- Total Harmonic Distortion: $\leq 1\%$ @ 1KHz, rated power
- Sensitivity: XLR, Phone Jack (Balanced) 1V, 100mV @ 10K Ω
- Outputs: 8 Ω , 70V, 100V
- Signal to Noise Ratio: 86 dB
- Indicator: Power On, Level
- AC Power Consumption: 640W
- DC Power Consumption: 15A
- Dimensions (mm): 88(H) x 425(W) x 305(D)
- Weight: 10.6 Kg
- Mounting options: Desktop or 19" rack



QTA-1360P power amp

- Output Power (RMS): 360W
- Power Supply: Main Voltage: AC 115V or 230V 50/60Hz, Battery Voltage: DC 24V
- Total Harmonic Distortion: $\leq 1\%$ @ 1KHz, rated power
- Sensitivity: XLR, Phone Jack (Balanced) 1V, 100mV @ 10K Ω
- Outputs: 8 Ω , 70V, 100V
- Signal to Noise Ratio: 86 dB
- Indicator: Power On, Level
- AC Power Consumption: 960W
- DC Power Consumption: 24A
- Dimensions (mm): 450 (W) x 285 (D) x 132 (H)
- Weight: 15 Kg
- Mounting options: Desktop or 19" rack



QTA-1480P power amp

- Output Power (RMS): 480W
- Power Supply: Main Voltage: AC 115V or 230V 50/60Hz, Battery Voltage: DC 24V
- Total Harmonic Distortion: $\leq 1\%$ @ 1KHz, rated power
- Sensitivity: XLR, Phone Jack (Balanced) 1V, 100mV @ 10K Ω
- Outputs: 8 Ω , 70V, 100V
- Signal to Noise Ratio: 86 dB
- Indicator: Power On, Level
- AC Power Consumption: 1280W
- DC Power Consumption: 30A
- Dimensions (mm): 450 (W) x 285 (D) x 132 (H)
- Weight: 17 Kg
- Mounting options: Desktop or 19" rack

